

Lagerkernprogramm 2009

- Gehobelt +/- 0,2/0,3 mm, Kanten gesägt
- Spannungsarm
- Wir fertigen nach DIN 16972 und DIN 2768m



PROlen 6000 REIN - UHMW- (~ 5,0 - 6,0 Mio/Mol)

mm	NATUR	GRÜN	SCHW	SCHW	NATUR	GRÜN	SCHW
	2050 x 1020 mm			AST+EL	2050 x 1250 mm		
10	x	x	x	x	x	x	x
12	x	x	x	x	x	x	x
15	x	x	x	x	x	x	x
20	x	x	x	x	x	x	x
25	x	x	x	x	x	x	x
30	x	x	x	x	x	x	x
40	x	x	x	x	x	x	x
50	x	x	x	x	x	x	x
60	x	x	x	x	x	x	x
70	x	x	x	x	x	x	x
80	x	x	x	x	x	x	x

PROlen 3000 RCM - regenerat - UHMW- (~ 3,0 - 4,0 Mio/Mol)

mm	NATUR	GRÜN	SCHW.	NATUR	GRÜN	SCHW
	3050 x 1020 mm			3050 x 1250 mm		
10	x	x	x	x	x	x
12	x	x	x	x	x	x
15	x	x	x	x	x	x
20	x	x	x	x	x	x
25	x	x	x	x	x	x
30	x	x	x	x	x	x
40	x	x	x	x	x	x
50	x	x	x	x	x	x
60	x	x	x	x	x	x
70	x	x	x	x	x	x
80	x	x	x	x	x	x

mm	GRÜN	SCHW	GRÜN	SCHW
	2050 x 1020 mm		2050 x 1250 mm	
10	x	x	x	x
12	x	x	x	x
15	x	x	x	x
20	x	x	x	x
25	x	x	x	x
30	x	x	x	x
40	x	x	x	x
50	x	x	x	x
60	x	x	x	x
70	x	x	x	x
80	x	x	x	x

mm	GRÜN	SCHW	GRÜN	SCHW
	3050 x 1020 mm		3050 x 1250 mm	
10	x	x	x	x
12	x	x	x	x
15	x	x	x	x
20	x	x	x	x
25	x	x	x	x
30	x	x	x	x
40	x	x	x	x
50	x	x	x	x
60	x	x	x	x
70	x	x	x	x
80	x	x	x	x

PROlen 500 REIN - HMW- (~ 0,5 Mio/Mol)

mm	NATUR	GRÜN	SCHW	NATUR	GRÜN	SCHW
	2050 x 1020 mm			2050 x 1250 mm		
10	x	x	x	x	x	x
12	x	x	x	x	x	x
15	x	x	x	x	x	x
20	x	x	x	x	x	x
25	x	x	x	x	x	x
30	x	x	x	x	x	x
40	x	x	x	x	x	x
50	x	x	x	x	x	x
60	x	x	x	x	x	x
70	x	x	x	x	x	x
80	x	x	x	x	x	x

PROlen 500 RCM - regenerat - HMW- (~ 0,5 Mio/Mol)

mm	NATUR	GRÜN	SCHW	NATUR	GRÜN	SCHW
	3050 x 1020 mm			3050 x 1250 mm		
10	x	x	x	x	x	x
12	x	x	x	x	x	x
15	x	x	x	x	x	x
20	x	x	x	x	x	x
25	x	x	x	x	x	x
30	x	x	x	x	x	x
40	x	x	x	x	x	x
50	x	x	x	x	x	x
60	x	x	x	x	x	x
70	x	x	x	x	x	x
80	x	x	x	x	x	x

mm	GRÜN	SCHW	GRÜN	SCHW
	2050 x 1020 mm		2050 x 1250 mm	
10	x	x	x	x
12	x	x	x	x
15	x	x	x	x
20	x	x	x	x
25	x	x	x	x
30	x	x	x	x
40	x	x	x	x
50	x	x	x	x
60	x	x	x	x
70	x	x	x	x
80	x	x	x	x

mm	GRÜN	SCHW	GRÜN	SCHW
	3050 x 1020 mm		3050 x 1250 mm	
10	x	x	x	x
12	x	x	x	x
15	x	x	x	x
20	x	x	x	x
25	x	x	x	x
30	x	x	x	x
40	x	x	x	x
50	x	x	x	x
60	x	x	x	x
70	x	x	x	x
80	x	x	x	x

Alle hier aufgeführten Artikel sind kurzfristig in handelsüblichen Mengen lieferbar.

PROFILAN Kunststoffwerk GmbH & Co. KG - Zur Dinkel 27-31 - D-48739 Legden - Telefon: (49)02566/93 33-0 - Telefax: (49)02566/93 33-33 - <http://www.profilan.de> - e-mail: info@profilan.de